

Downhole Flow Control Equipment

8 Standing Valves Plug Assembly

8.2 RR Standing Valve Plug Assembly

RR Standing Valve Plug Assembly is designed to hold pressure from above, and is best suited for applications such as testing the tubing string and setting packers. It is available in a wide variety of materials, and can be designed to work with a number of lock sizes and types. It is designed to be deployed

by threading to the bottom of the lock, or below an equalizing valve if equalization is required prior to retrieval. RR standing valve plugs are made up on R or RN lock mandrels and installed in R or RN landing nipples.

Available tool sizes as shown. Please contact our sales office for further enquiries.

R/RN Landing Nipple Size	R/RN Lock Mandrel Size	Fishneck Neck I.D.	GS+GU To Latch Nominal
2 7/8"	2.188"	1.81"	2.5"
2 7/8"	2.313"	1.81"	2.5"
3 1/2"	2.562"	1.81"	2.5"
3 1/2"	2.875"	2.31"	3"
4"	3.125"	2.62"	3.5"
4"	3.250"	2.62"	3.5"
4 1/2"	3.437"	2.62"	3.5"
4 1/2"	3.688"	3.12"	4"
4 1/2"	3.813"	3.12"	4"
5"	4.125"	3.12"	4"
5 1/2"	4.313"	3.12"	4"
5 1/2"	4.562"	4.00"	5"
7"	5.875"	4.75"	6"
7"	5.963"	4.75"	6"

