

Running, Shifting and Positioning Tools

1 Type X Running Tools

Type X Running Tool is designed to run and set Type X or Type XN Lock Mandrel in the corresponding Landing Nipple in the well. It comes in 2 settings: selective and non-selective. When runs in selective setting, it can be run pass Nipples and selectively choose which nipple to set the Lock Mandrel. For

non-selective setting, the lock is usually set on the highest nipple profile in the tubing or the bottom No-Go Nipple profile.

Type X Running Tool is used in conjunction with Type X Lock Mandrel. Please refer to Type X Lock Mandrel for more information.

Available tool sizes as shown. Please contact our sales office for further enquiries.

To Suit Lock Mandrel Size	Tools O.D.	Fishneck O.D.	Top Connection	Bottom Connection
1.875"	1.772"	1.375"	15/16" -10UN	1/2" -13UN
2.313"	2.209"	1.750"	15/16" -10UN	5/8" -11UN
2.750"	2.720"	2.313"	1 1/16"-10UN	3/4" -10UN
2.813"	2.720"	2.313"	1 1/16"-10UN	3/4" -10UN
2.875"	2.840"	2.313"	1 1/16"-10UN	3/4" -10UN
3.313"	3.250"	2.313"	1 1/16"-10UN	1 3/8" -12UN
3.813"	3.750"	2.313"	1 1/16"-10UN	2 1/8" -12UN
4.313"	4.280"	2.313"	1 1/16"-10UN	2 1/8" -12UN
4.562"	4.500"	3.125"	1 1/16"-10UN	2 1/2" -10UN

Toolstring Equipment



www.wellservpec.com