

# Running, Shifting and Positioning Tools

## 3 Type RX Running Tool

**Type RX Running Tool** set X,XN,R,RN,and RQ Lock Mandrels in their respective landing nipples.This tool is generally used for installing tubing safety valves in the uppermost landing nipple.With this tool,the lock mandrel may be run with the keys in the control or locating positions.The lock mandrel keys or no-go serve to locate the nipple rather than the dogs

on the running tool.When a non no-go lock is being run,the keys must be run in the locating position and the lock must be set in the first nipple in the bore of that lock size.The tool gives a positive indication when the lock is fully set.

Available tool sizes as shown. Please contact our sales office for further enquiries.

To Suit Lock Mandrel Size	Tools O.D.	Fishneck O.D.	Top Connection	Bottom Connection
2.313"	2.120"	1.750"	15/16" -10UN	5/8" -11UN
2.750"	2.690"	2.313"	1 1/16"-10UN	1 1/4"-12UN
2.813"	2.690"	2.313"	1 1/16"-10UN	1 1/4"-12UN
2.875"	2.620"	2.313"	1 1/16"-10UN	1 1/4"-12UN
3.125"	3.090"	2.313"	1 1/16"-10UN	1 3/8" -12UN
3.313"	3.090"	2.313"	1 1/16"-10UN	1 3/8" -12UN
3.437"	3.090"	2.313"	1 1/16"-10UN	1 3/8" -12UN
3.688"	3.620"	2.313"	1 1/16"-10UN	1 7/8" -12UN
3.813"	3.620"	2.313"	1 1/16"-10UN	2 1/8" -12UN
4.125"	3.620"	2.313"	1 1/16"-10UN	2 1/8" -12UN
4.562"	4.500"	3.125"	1 1/16"-10UN	2 1/2"-10UN
5.875"	5.810"	3.125"	1 1/16"-10UN	3 3/8" -12UN
5.963"	5.810"	3.125"	1 1/16"-10UN	3 3/8" -12UN

Toolstring Equipment



[www.wellservpec.com](http://www.wellservpec.com)