

WELL COMPLETION TOOLS



SCP COMPOSITE BRIDGE PLUG

Model SCP Composite Bridge Plugs are used for temporary or permanent isolation of oil, gas and water, such as zone isolation, formation fracturing and acidizing. These easy drillable bridge plugs can be used for multi-zone fracturing, so it is an especially good choice for shale gas exploration.


SCP-P Solid body

SCP-F No-solid body

SCP-D No-solid body, cage type

Features:

- Can be set directly with SWSG/SWSB wireline or SHSG/SHSB hydraulic setting tool
- Easy for mill out
- Slope bottom can stop the rotation of the bridge plug
- The working temperature is below 150°C(300°F)



SPECIFICATIONS

Part number	Model	Size	Casing Wt	Dimension			Setting range		Release force	Pressure	Temp
				OD	ID	Length	Min	Max			
				inch	inch	inch	inch	inch			
D124082300	SCP-P (Solid body)	4"	5.6~14#	3.22	~	23.64	3.320	3.548	33,000	10K	300
D124582300		4 1/2"	9.5~15.1#	3.61	~	23.01	3.826	4.090	33,000	10K	300
D125082300		5"	11.5~21#	3.92	~	26.71	4.126	4.560	33,000	10K	300
D125582300		5 1/2"	15.5~23#	4.39	~	26.71	4.670	4.950	33,000	10K	300
D127082300		7"	23~32#	5.63	~	34.92	6.094	6.366	55,000	10K	300
D144082300	SCP-F (No-solid body, ball type)	4"	5.6~14#	3.19	0.75	23.65	3.320	3.548	33,000	10K	300
D144582300		4 1/2"	9.5~15.1#	3.61	0.75	23.01	3.826	4.090	33,000	10K	300
D145082300		5"	11.5~21#	3.92	0.75	26.71	4.126	4.560	33,000	10K	300
D145582300		5 1/2"	15.5~23#	4.39	1.00	26.71	4.670	4.950	33,000	10K	300
D147082300		7"	23~32#	5.63	1.50	34.38	6.091	6.366	55,000	10K	300
D144082301	SCP-D (cage type)	4"	5.6~14#	3.19	0.75	23.65	3.320	3.548	33,000	10K	300
D144582301		4 1/2"	9.5~15.1#	3.61	0.75	23.01	3.826	4.090	33,000	10K	300
D145082301		5"	11.5~21#	3.92	0.75	26.71	4.126	4.560	33,000	10K	300
D145582312		5 1/2"	15.5~23#	4.39	1.00	26.49	4.670	4.950	33,000	10K	300
D147082301		7"	23~32#	5.63	1.50	34.38	6.091	6.366	55,000	10K	300

