WELL COMPLETION TOOLS

SHC PACKER (Y341)

The SHC Packers is used in injection, formation fracturing, acidizing and squeeze cementing. It has hydraulic setting, and can be used solely or with other packers as a combination. Hydraulic anchor is recommended with the string to enhance the stability.

Features:

- Sets securely in any hardness casing, including premium grades
- Suitable for highly-deviated well
- Hydraulically activated, hydrostatic set
- Built-in bypass
- Triple seal multi-durometer elements

SPECIFICATIONS

| Part number | Casing OD | Casing Wt | Setting range | | Tool OD | Tool ID | l ID Connection thread | |
|--------------|-----------|-----------|---------------|---------|---------|---------|---------------------------|--|
| | (in) | (lbs/ft) | Min(in) | Max(in) | (in) | (in) | connection tifead | |
| D33-0550-003 | 5 1/2 | 20.0-23.0 | 4.625 | 4.778 | 4.5 | 2 | 2 7/8"-8RD EU | |
| D33-0550-001 | | 15.5-20.0 | 4.778 | 4.95 | 4.64 | | | |
| D33-0550-002 | | 13.0-15.5 | 4.95 | 5.19 | 4.78 | | | |
| D33-0700-001 | 7 | 38 | 5.83 | 5.937 | 5.65 | 2.44 | 2 7/8"-8RD EU | |
| D33-0700-002 | | 32.0-35.0 | 5.938 | 6.135 | 5.81 | | | |
| D33-0700-003 | | 26.0-29.0 | 6.136 | 6.276 | 5.97 | | | |
| D33-0700-004 | | 20.0-26.0 | 6.276 | 6.456 | 6.07 | | | |
| D33-0700-005 | | 17.0-20.0 | 6.456 | 6.578 | 6.27 | | | |



HT

CO,

