

HT CO<sub>2</sub> H<sub>2</sub>S



## SMP PULL-PUSH TYPE PACKER

Model SMP Pull-Push Type Packers are used for testing and zonal isolation application. The packers will be set when uplift and put down and unset by uplifting. It is simple structure and reliable functionality.

### Features:

- Sets securely in any hardness casing, including premium grades
- Three-piece packing element system
- The length is moderate for running in
- Can be used with hydraulic anchor and circulation valve for formation fracturing

### SPECIFICATIONS

Part number	Casing OD	Casing Wt	Setting range		Tool OD	Tool ID	Connection thread
	(in)	(lbs/ft)	Min(in)	Max(in)	( in )	(in)	
D43-5010-300	5	15-18	4.25	4.408	4.125	1.81	2 7/8"-8RD EU
D43-5510-300	5 1/2	20.0-23.0	4.625	4.778	4.50	1.94	
D43-5510-301	5 1/2	15.5-20.0	4.778	4.95	4.64	1.94	
D43-7010-301	7	38	5.83	5.937	5.65	2.38	
D43-7010-300	7	32.0-35.0	5.938	6.135	5.81	2.38	
D43-7010-302	7	26.0-29.0	6.136	6.276	5.97	2.38	
D43-7010-303	7	20.0-26.0	6.276	6.456	6.07	2.38	
D43-7010-304	7	17.0-20.0	6.456	6.578	6.27	2.38	