

# WELL COMPLETION TOOLS



## STA TUBING ANCHOR

Model STA Tubing Anchor/Catchers are used to allow placement of tubing in tension. Vertical tubing movement is prevented, which in turn lessens sucker rod tubing wear. Their small o.d. and large i.d. permits larger volume production capacities. These fully retrievable tools can be easily adjusted for emergency release by adding or removing shear pins. They are available for 4 1/2" through 7 5/8" casings.

### Features:

- Sets securely in any hardness casing, including premium grades
- Large bore
- Small OD
- Model "R" left hand release or emergency shear release, Model "L" right hand release or emergency shear release
- Easy adjusted release from 5,000 lbs to 60,000 lbs
- Drag blocks rather than drag springs



### SPECIFICATIONS

Part number	Casing OD	Casing Wt (lbs/ft)	Setting range		Tool OD (in)	Tool ID (in)	Connection thread	
	(in)		Min(in)	Max(in)				
D08-0450-001(R)	4 1/2	9.5-13.5	3.920	4.090	3.75	1.93	2 3/8"-8RD EU	
D08-0450-201(L)								
D08-0500-201(L)	5	13.0-18.0	4.276	4.491	4.00			
D08-0500-001(R)								
D08-0550-201(L)	5 1/2	13.0-23.0	4.670	5.044	4.50	2.00	2 7/8"-10RD NU	
D08-0550-001(R)								
D08-0550-210(L)								
D08-0550-010(R)								
D08-0711-201(L)	7	23.0-40.0	5.920	6.580	5.50			
D08-0700-001(R)								
D08-0700-210(L)	7	17.0-38.0	5.920	6.580	5.76	3.00		3 1/2"-8RD EU
D08-0700-010(R)								
D08-0700-202(L)						2.37	2 7/8"-8RD EU	
D08-0700-002(R)								

R—right hand setting L—left hand setting